

On Demand Grinders

Technical specifications

Model	800 RS	800	700	600
Voltage	220-240V	220-240V	220-240V	220-240V
	50-60 hz	50-60 hz	50-60 hz	50-60 hz
Power	500 W	500 W	400 W	300 W
Rpm 50hz / 60hz	1480 / 1700	1480 / 1700	1480 / 1700	1380 / 1650
Average output (g/s)*	3,5 (50hz)	3,5 (50hz)	3 (50hz)	1,7 (50hz)
	4,2 (60hz)	4,2 (60hz)	3,6 (60hz)	2 (60hz)
Net weight	11,0 kg	11,0 kg	9,8 kg	7,8 kg
Gross weight	12,6 kg	12,6 kg	11,0 kg	8,9 kg
Dimensions	178x212x620h mm	178x212x620h mm	178x212x590h mm	178x212x550h mm
Burrs	ø83 Flat burrs	ø83 Flat burrs	ø64 Flat burrs	ø64 Flat burrs
	Red Speed			
Hopper	Capacity 1600 g	Capacity 1600 g	Capacity 1600 g	Capacity 600 g
Grinding adjustment type	Micrometrical	Micrometrical	Micrometrical	Micrometrical
	stepless	stepless	stepless	stepless
Dose setting	Digital	Digital	Digital	Digital
Display	Touch	Touch	Touch	Touch
PFA	Available	Available	Available	Available
Dosing	Free & Pre-set	Free & Pre-set	Free & Pre-set	Free & Pre-set
Start	Pulse button	Pulse button	Pulse button	Pulse button

Note: Additional voltage models available.

*Average output is calculated at standard Italian Espresso Consistency

Doser Grinders

Technical specifications

Model	800D RS	800D	700D
Voltage	220-240V	220-240V	220-240V
	50-60 hz	50-60 hz	50-60 hz
Power	500 W	500 W	400 W
Rpm 50hz / 60hz	1480 / 1700	1480 / 1700	1380 / 1650
Net weight	12,5 kg	12,5 kg	11,0 kg
Gross weight	14,3 kg	14,3 kg	12,6 kg
Dimensions	200x275x620h mm	200x275x620h mm	200x275x590h mm
Burrs	ø83 Flat burrs	ø83 Flat burrs	ø64 Flat burrs
Hopper			
	Capacity 1600 g	Capacity 1600 g	Capacity 1600 g
Grinding adjustment type	Micrometrical	Micrometrical	Micrometrical
	stepless	stepless	stepless
Doser capacity	280 g	280 g	280 g
Dose adjustment	6 ÷ 9,5 g	6 ÷ 9,5 g	6 ÷ 9,5 g

Note: Additional voltage models available.

*Average output is calculated at standard Italian Espresso Consistency